



For: MULTI-NODE POINT-TO-POINT SATELLITE COMMUNICATION SYSTEM EMPLOYING MULTIPLE GEO SATELLITES




FIG. 1




FIG. 2



For: MULTI-NODE POINT-TO-POINT SATELLITE COMMUNICATION SYSTEM EMPLOYING MULTIPLE GEO SATELLITES




FIG. 3




FIG. 4



Drawing Sheet Fig. 5

Sheet 3 of 5

Serial No. 09/576,652 - Filed May 22, 2000

Frank A. Hagen, et al.

For: MULTI-NODE POINT-TO-POINT SATELLITE COMMUNICATION SYSTEM EMPLOYING MULTIPLE GEO SATELLITES




FIG. 5

Fringe Phase and Power

The graph displays three curves against Distance from Nadir (km) on a logarithmic scale from 0.01 to 10,000 km.

- Pathlength Difference (dashed line):** Increases linearly on the log-log scale, starting at approximately 0.5 wavelengths at 0.01 km and reaching 10,000 wavelengths at 10,000 km.
- Single Channel Envelope (118) (solid line):** Shows a sharp drop from 1.0 at 0.01 km to near zero by 0.2 km, with a small secondary peak around 1 km.
- Total Bandwidth Envelope (116) (dotted line):** Shows a sharp drop from 1,000,000 at 0.01 km to near zero by 0.2 km, with a small secondary peak around 1 km.

Legend:

- Pathlength Difference
- Single Channel Envelope (118)
- Total Bandwidth Envelope (116)



For: MULTI-NODE POINT-TO-POINT SATELLITE COMMUNICATION SYSTEM EMPLOYING MULTIPLE GEO SATELLITES





FIG.8



Orbital Parameters:

Altitude:

Longitude of Ascending Node:

Inclination (i):

Eccentricity:

Argument of Perigee

Sat0

GEO

100°W

0°

--

--

Sat1

GEO

110°W

10°

0.087 = $\sqrt{2}$

90°

FIG.9